## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	FERMOB

Supplier's address: SERVICE RELATION CLIENT, PARC ACTIV	AL, 01140 THOISSEY, FR
---	------------------------

Model identifier:	5303-MOOON!-LAMPE	H.41
-------------------	-------------------	------

_	•			
Tyna	Λt	lioht	source	٠.
IVDE	vı	HEILL	JUUILE	- •

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	Diffuseur verre			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:	Yes	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	Yes	Dimmable:	No	
Product parameters				
Parameter	Value	Parameter	Value	
General product parameters:				

Darameter		Value	Darameter	Value
Parameter		Value	Parameter	Value
		General product p	1	
<u> </u>	nption in on- 00 h), rounded st integer	3	Energy efficiency class	F
indicating if it re in a sphere (36	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	250 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000 or 6 000
On-mode p expressed in W	oower (P <sub>on</sub> ),	2,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
	dby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	81
Outer	Height	410	Spectral power	See image
dimensions	Width	150	distribution in the	in last page
without	Depth	150		Page 1 / 3

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,311
Parameters for LED and OLED light sources:			
R9 colour rendering index value	-10	Survival factor	1,00
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

