## **Product Information Sheet**

without

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

	COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources						
	Supplier's name or trade mark: Fatboy the Original B.V.						
	<b>Supplier's address:</b> Fatboy the Original B.V., Het Zuiderkruis 3, 5215 MV 's-Hertogenbosch, NL <b>Model identifier:</b> Bolleke						
	Type of light source:						
	Lighting technol	ogy used:	LED	Non-directional or directional:	NDLS		
	Light source cap	-type	Integrated LED				
	(or other electric interface)						
	Mains or non-m	ains:	NMLS	Connected light source (CLS):	No		
	Colour-tuneable	light source:	No	Envelope:	-		
	High luminance	light source:	No				
	Anti-glare shield	l:	No	Dimmable:	Yes		
			Product para	meters			
	Parameter		Value	Parameter	Value		
	Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		General product p	Energy efficiency class	А		
	Useful luminou indicating if it re in a sphere (36 cone (120º) or in (90º)	efers to the flux 50º), in a wide	38 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
	On-mode power (P <sub>on</sub> ), expressed in W		1,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
	Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	68		
	Outer dimensions	Height Width	200	Spectral power distribution in the	See image in last page		
		VVICITI	200	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	1 - 7   0 -		

200

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,465		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	5	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

