## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	e or trade mark:	LEDVANCE		
Supplier's addr	ess: LEDVANCE G	mbH, Parkring 33, G	Garching, Germany	
Model identifie	er: AC34675			
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)		constant current: 460 mA		
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	No
		Product para		I
Parameter		Value	Parameter	Value
		General product p	T	Ι
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		17	Energy efficiency class	E
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30006500
On-mode power (P <sub>on</sub> ), expressed in W		17,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions	Height	928	Spectral power	See image
	Width	9	distribution in the	in last page
without	Depth	1		Pag

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,434			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

